CP4195 - OLYMPIA™ 34" Bowl, Power Art Cable



Project: Type:

VisaLighting.com/products/Olympia

Fill in shaded boxes using information listed below

Order CP4195 Code: MODEL










(S) OPTION(S)





MVOLT fixture accepts 120 through 277 input voltage LED Sources are dimmable 0-10V to 10% and are 83CRI, within 3-step MacAdam

	LED Sources	ССТ	Uplight		Dow		
			Delivered Lumens	Power (Watts)	Delivered Lumens	Power (Watts)	Voltage
•	L30K	3000K	12600		4100	53	MVOLT
	L35K	3500K	13100	119	4300		
•	L40K	4000K	13500		4400		

FINISHES (Select one)

See page 2 for color chart

Powder Coat Painted Finishes (Standard)

AG7038	Agate Grey	CVBL	Cove Blue	GW9002	Grey White	PB1035	Pearl Beige
BMAT	Bronze Matte	CW9001	Cream	HTHR	Heather	RUST	Rust
BRNZ	Bronze	GLIM	Glimmer	JB9005	Jet Black	SUNG	Sungold
BSIL	Blade Silver	GSIL	Graphite Silver	OBRZ	Old Bronze	TW9016	Traffic White

Metal Finishes (Premium)

BA Brushed Aluminum **BUA** Brushed Copper Alternative Brushed Brass **BZA** Brushed Bronze Alternative

BBA Brushed Brass Alternative **OBA** Oil-Rubbed Bronze Alternative

BCA Brushed Chrome Alternative Polished Brass **PRA** Pewter Alternative

RBA Rustic Brass Alternative

SNA Satin Nickel Alternative

DIFFUSER OPTION

Diffuser is matte white acrylic unless ABA option is selected

This complete family includes pendants, flush mount ceiling units and wall sconces that showcase a

X = Body Height

refined, contemporary trim. The luminous acrylic and traditional detailing enhance a wide range

OAH = Overall Height

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(36) indicates an overall fixture height of 36"

Hand Painted Alabaster Alternative ABA

OPTIONS (Multiple Selections Allowed)

A Option availability may be interdependent with Voltage, Source or Other Options

ΑF Add Finial. Addition of **AF** option increases X dimension (height) by 1-1/8"

DCC Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations)

XPS Express 10 day shipping. Items marked with a bullet (•) are not available with XPS

● A OAH must be specified

DIMENSIONS

W=Width

of architectural settings and styles.

NBS = Nominal Bowl Size MP = Stem Accent Midpoint

W 33-7/8" (860 mm) OAH 32" (813 mm) 91 (229 mm) NBS 31x7" (787x178 mm) 26-1/8" (664 mm)



AF Option











LFD


FTL Listed

5 Year Warranty

CP4195 - OLYMPIA 34" Bowl, Power Art Cable



Photometrics



Technical Information

- Integral power supply
- Fixture tested per LM79 standard
- Modular design for replacement of LED source and power supply
- Easy tool-less bowl cleaning
 Patented Power Art Cable™ mounting system uses a braided stainless steel jacket to encapsulate power conductors and provide support. Mounts to junction box rated for 50# loads
- Mounts to standard electrical junction box (by others) with provided hardware for sloped ceiling up to 45 degrees from horizontal
- Spun metal trim
- Thermally formed 1/8" thick white acrylic diffuser with matte finish
 - UV stable

OBA

Oil-Rubbed Bronze

Alternative

- UL-94 HB Flame Class rated
- No VOC powder coat paint finish; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suited for exterior applications

Relative Scale Drawing Door Height = 7 Ceiling Height = 11' Silhouette Height = 6'

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>

For additional information see <u>VisaLighting.com/materials-finishes</u>

Painted Finishes (Standard)



This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. @Visa Lighting. Design Modification Rights Reserved

PRA

Pewter Alternative

RBA

Rustic Brass

Alternative

SNA

Satin Nickel

Alternative

PB

Polished Brass